



User information for Albrecht 10 m transceivers Frequency extension to 454 Channel system

All our 10 m all mode transceivers AE 485 S, AE 497 S, Alphaforce, Deltaforce and AE 201S can be switched **temporarily** from frequency mode 28-29.7 MHz into "channel mode". The list of frequencies and channels can be found on the next page.

After the conversion, the radio can be used from 25.165 MHz to 29.695 MHz. While Albrecht specifications are only valid for the amateur range starting with 28.000 MHz, Albrecht cannot guarantee correct operation on extended frequencies, especially on the lower channels. It may happen that the transceiver operate with less performance (output and sensitivity) or does even not lock in on all frequencies outside of the specified amateur radio range.

Note: Only authorized users are allowed to operate on these frequencies! Even if You should have a valid amateur radio operator's licence it is not allowed to use channels or frequencies outside of the dedicated amateur radio band. The regulations may vary from country to country. Users are requested to fulfill all national user requirements for operating the radio.

Switching to 454 CHANNEL MODE:

AE 201 S:

Just press **FUNCTION** button, then press **CALL** and hold this key pressed for about 3 seconds. Release button and the unit works on 454 Channels until the radio will be later switched off again.

If You have once switched to 454 channels, You can also **toggle between channel number and frequency display** by pressing **FUNCTION + CALL**, but this only by touching the call button for short time.

AE 495 S and AE 497 S: same procedure, but here the correct buttons are the "**FUNCTION**" and the "**2**" buttons.

DeltaForce, AlphaForce: These radios have a jumper, which must be cut before the above described switching procedure will be possible. The jumper is accessible without opening the radio: Disconnect from power, tear off the channel knob, behind the knob You will see a cable, which must be cut.

Channel number	Band A	B	C	D	E	F	G	H	I	J
1	25.165	25.615	26.065	26.515	26.965	27.415	27.865	28.315	28.765	29.215
2	25.175	25.625	26.075	26.525	26.975	27.425	27.875	28.325	28.775	29.225
3	25.185	25.635	26.085	26.535	26.985	27.435	27.885	28.335	28.785	29.235
3A	25.195	25.645	26.095	26.545	26.995	27.445	27.895	28.345	28.795	29.245
4	25.205	25.655	26.105	26.555	27.005	27.455	27.905	28.355	28.805	29.255
5	25.215	25.665	26.115	26.565	27.015	27.465	27.915	28.365	28.815	29.265
6	25.225	25.675	26.125	26.575	27.025	27.475	27.925	28.375	28.825	29.275
7	25.235	25.685	26.135	26.585	27.035	27.485	27.935	28.385	28.835	29.285
7A	25.245	25.695	26.145	26.595	27.045	27.495	27.945	28.395	28.845	29.295
8	25.255	25.705	26.155	26.605	27.055	27.505	27.955	28.405	28.855	29.305
9	25.265	25.715	26.165	26.615	27.065	27.515	27.965	28.415	28.865	29.315
10	25.275	25.725	26.175	26.625	27.075	27.525	27.975	28.425	28.875	29.325
11	25.285	25.735	26.185	26.635	27.085	27.535	27.985	28.435	28.885	29.335
11A	25.295	25.745	26.195	26.645	27.095	27.545	27.995	28.445	28.895	29.345
12	25.305	25.755	26.205	26.655	27.105	27.555	28.005	28.455	28.905	29.355
13	25.315	25.765	26.215	26.665	27.115	27.565	28.015	28.465	28.915	29.365
14	25.325	25.775	26.225	26.675	27.125	27.575	28.025	28.475	28.925	29.375
15	25.335	25.785	26.235	26.685	27.135	27.585	28.035	28.485	28.935	29.385
15A	25.345	25.795	26.245	26.695	27.145	27.595	28.045	28.495	28.945	29.395
16	25.355	25.805	26.255	26.705	27.155	27.605	28.055	28.505	28.955	29.405
17	25.365	25.815	26.265	26.715	27.165	27.615	28.065	28.515	28.965	29.415
18	25.375	25.825	26.275	26.725	27.175	27.625	28.075	28.525	28.975	29.425
19	25.385	25.835	26.285	26.735	27.185	27.635	28.085	28.535	28.985	29.435
19A	25.395	25.845	26.295	26.745	27.195	27.645	28.095	28.545	28.995	29.445
20	25.405	25.855	26.305	26.755	27.205	27.655	28.105	28.555	29.005	29.455
21	25.415	25.865	26.315	26.765	27.215	27.665	28.115	28.565	29.015	29.465
22	25.425	25.875	26.325	26.775	27.225	27.675	28.125	28.575	29.025	29.475
23	25.455	25.905	26.355	26.805	27.255	27.705	28.155	28.605	29.055	29.505
24	25.435	25.885	26.335	26.785	27.235	27.685	28.135	28.585	29.035	29.485
25	25.445	25.895	26.345	26.795	27.245	27.695	28.145	28.595	29.045	29.495
26	25.465	25.915	26.365	26.815	27.265	27.715	28.165	28.615	29.065	29.515
27	25.475	25.925	26.375	26.825	27.275	27.725	28.175	28.625	29.075	29.525
28	25.485	25.935	26.385	26.835	27.285	27.735	28.185	28.635	29.085	29.535
29	25.495	25.945	26.395							